

TECNICAL DATA SHEET

CEM I 52,5 N - Milke® classic

Plant Milke, Geseke

Page 1 of 2

Composition

CEM I 52.5 N Milke® classic is a Portland cement complying with DIN EN 197-1. It consists of Portland cement clinker and a sulfate compound, which is needed as a setting regulator. The optimized production process ensures a high degree of uniformity of the cement. As a low-chromium cement, a small amount of a chromium-reducing additive may also be included.

Properties

Due to its high Portland cement clinker content, CEM I 52.5 N Milke® classic has a high initial strength. The cement exhibits good compatibility and effectiveness with construction chemical additives such as plasticizers, retarders, accelerators, dispersion powders, etc., and is thus especially well suited for the production of dry mortar systems. The cement complies with EU Directive EC 1907/2006 for low chromium levels.

Area of Application

CEM I 52.5 N Milke® classic lends itself to applications in which an increased early strength and final strength development is desired. Due to its good processability, it is especially well suited for use in factory-produced dry mortars, such as tile adhesives, self-leveling compounds, fillers and leveling compounds, grout mortars, etc.

CEM I 52.5 N Milke® classic meets the requirements for cements according to DIN EN 480-1. It is suitable for the production of reference concrete/mortar for the testing of additives for concrete, mortar and grout.

Processing Instructions

In order to take advantage of the full potential of the cement, the accepted rules of the trade, such as adequate curing to protect against desiccation and freezing, must be applied. Contact with the skin and eyes must be avoided when working with cement. Individual safety measures, such as gloves and protective eyewear, are prescribed.

Verkauf und Beratung

Heidelberg Materials AG, Verkaufsregion Nord

Zur Anneliese 7

59320 Ennigerloh

Tel.: + 49 2524 2951-271

mailto: zement.vertriebnord@heidelbergmaterials.com

www.heidelbergmaterials.de



**Heidelberg
Materials**

TECNICAL DATA SHEET

CEM I 52,5 N - Milke® classic

Plant Milke, Geseke

Page 2 of 2

Monitoring

CEM I 52.5 N Milke® classic is subject to in-plant production inspection according to the conformity criteria defined by DIN EN 197-1 and is monitored by the Verein Deutscher Zementwerke e.V. (VDZ).

Delivery

CEM I 52.5 N Milke® classic is supplied exclusively as bulk goods in a silo truck.

Storage

Cements are sensitive to moisture and should therefore be stored in a dry place and protected from moisture. With proper storage, the low-chromium property of this cement is guaranteed for the following period:

- 12 months from loading date

Stand unverändert seit: Mai 2023

Der Geschäftsbereich Zement/Deutschland der Heidelberg Materials AG ist zertifiziert nach vdz-Cert – DIN EN ISO 50001 sowie DIN EN ISO 9001 und 14001 – Reg. Nr. 0081/21. Die Angaben in dieser Druckschrift basieren auf unseren derzeitigen technischen Kenntnissen und Erfahrungen und erfolgen ohne Gewähr. Sie befreien den Verarbeiter wegen der Fülle möglicher Einflüsse bei Verarbeitung und Anwendung unserer Produkte nicht von eigenen Prüfungen und Versuchen und stellen nur allgemeine Richtlinien dar. Eine rechtlich verbindliche Garantie bestimmter Eigenschaften oder der Eignung für einen konkreten Einsatzzweck kann hieraus nicht abgeleitet werden. Etwaige Schutzrechte sowie bestehende Gesetze und Bestimmungen sind vom Verarbeiter stets in eigener Verantwortung zu beachten.

Verkauf und Beratung

Heidelberg Materials AG, Verkaufsregion Nord

Zur Anneliese 7

59320 Ennigerloh

Tel.: + 49 2524 2951-271

mailto: zement.vertriebnord@heidelbergmaterials.com

www.heidelbergmaterials.de



**Heidelberg
Materials**