

CEM I 52,5 R - Milke® premium

Plant Milke, Geseke

Page 1 of 2

Composition

CEM I 52.5 R Milke® premium is a Portland cement complying with DIN EN 197-1. It consists of Portland cement clinker and a sulfate compound, which is needed as a setting regulator. The optimized production process ensures a high degree of uniformity of the cement. As a low-chromium cement, a small amount of a chromium-reducing additive may also be included.

Properties

Due to its high Portland cement clinker content, CEM I 52.5 R Milke® premium has a high initial strength and high final strengths. The cement exhibits good compatibility and effectiveness with construction chemical additives such as plasticizers, retarders, accelerators, dispersion powders, etc., and is thus especially well suited for the production of dry mortar systems. The cement complies with EU Directive EC 1907/2006 for low chromium levels.

Area of Application

CEM I 52.5 R Milke® premium lends itself to applications in which a high early strength and final strength development is desired. Due to its good processability, it is especially well suited for use in factory-produced dry mortars such as grout compounds, screed compounds, self-leveling floor filling and leveling compounds, tile adhesives, grout mortars, SPCC mortars, repair mortars, etc.

Processing Instructions

In order to take advantage of the full potential of the cement, the accepted rules of the trade, such as adequate curing to protect against desiccation and freezing, must be applied. Contact with the skin and eyes must be avoided when working with cement. Individual safety measures, such as gloves and protective eyewear, are prescribed.

Verkauf und Beratung

Heidelberg Materials AG, Verkaufsregion Nord

Zur Anneliese 7

59320 Ennigerloh

Tel.: + 49 2524 2951-271

mailto: zement.vertriebnord@heidelbergmaterials.com

www.heidelbergmaterials.de



CEM I 52,5 R - Milke® premium

Plant Milke, Geseke

Page 2 of 2

Monitoring

CEM I 52.5 R Milke® premium is subject to in-plant production inspection according to the conformity criteria defined by DIN EN 197-1 and is monitored by the Verein Deutscher Zementwerke e.V. (VDZ).

Delivery

CEM I 52.5 R Milke® premium is supplied exclusively as bulk goods in a silo truck.

Storage

Cements are sensitive to moisture and should therefore be stored in a dry place and protected from moisture. With proper storage, the low-chromium property of this cement is guaranteed for the following period:

- 12 months from loading date

Stand unverändert seit: Mai 2023

Der Geschäftsbereich Zement/Deutschland der Heidelberg Materials AG ist zertifiziert nach vdz-Cert – DIN EN ISO 50001 sowie DIN EN ISO 9001 und 14001 – Reg. Nr. 0081/21. Die Angaben in dieser Druckschrift basieren auf unseren derzeitigen technischen Kenntnissen und Erfahrungen und erfolgen ohne Gewähr. Sie befreien den Verarbeiter wegen der Fülle möglicher Einflüsse bei Verarbeitung und Anwendung unserer Produkte nicht von eigenen Prüfungen und Versuchen und stellen nur allgemeine Richtlinien dar. Eine rechtlich verbindliche Garantie bestimmter Eigenschaften oder der Eignung für einen konkreten Einsatzzweck kann hieraus nicht abgeleitet werden. Etwaige Schutzrechte sowie bestehende Gesetze und Bestimmungen sind vom Verarbeiter stets in eigener Verantwortung zu beachten.

Verkauf und Beratung

Heidelberg Materials AG, Verkaufsregion Nord

Zur Anneliese 7

59320 Ennigerloh

Tel.: + 49 2524 2951-271

mailto: zement.vertriebnord@heidelbergmaterials.com

www.heidelbergmaterials.de

